







Meter Service Fittings are manufactured in accordance with the highest technical standards which guarantee:

• Mechanical requirements are met for the specific need of meter installations.

• Insulating requirements are achieved and surpass the electrical characteristics of the product transported through the pipe.

When ordering, please give the following information:

- 1. Diameter of pipe
- 2. Style, Male/Male, Male/Female, Female/Female, Weld/Male, Weld/Female, Weld/Weld

Water Service Fittings

Now available from APS, Copper to Steel Water Service Fittings for Water Service Lines.

Available: MxM NPT Thread MxF NPT Thread MNPT x Weld FNPT x Weld Weld x Weld F x F NPT Steel
Polycarbonate Insulation
Copper
Polycarbonate Insulation
Copper

Inside Dia.	А	A1	В	С	D	F1	F2	F3	F4	F5	F6	G	S	S1
¹ /2"	1 ¹³ /16"	1"	13/16"	3/4"	1 1/8"	3 11/16"	5 ⁷ / ₁₆ "	8 ³ /16"	5 ⁷ / ₁₆ "	3 3/4"	1"	1 ¹ /16"	5/32"	1/8"
3/4"	1 ¹⁵ /16"	2 ¹ /16"	1 ¹ /16"	³ /4"	1 ³ /16"	3 ¹⁵ / ₁₆ "	6 ⁵ /8"	9 ³ /8"	6 ⁵ /8"	3 ¹⁵ /16"	3 ¹ /16"	1 ¹ /4"	5/32"	1/8"
1"	2 ³ /16"	2 ³ /8"	1 ⁵ /16"	³ /4"	1 ¹ /4"	4 ¹¹ / ₁₆ "	7 ¹ /4"	9 ¹ /2"	7 ¹ /4"	4 ¹ /16"	3 7/16"	1 ¹ /2"	⁵ /32"	5/32"
1 ¹ /4"	2 1/2"	2 ³ /4"	1 11/16"	⁷ /8"	1 ³ /8"	5 ¹ /4"	8 ³ /16"	10 ¹ /2"	8 ³ /16"	4 ⁷ /16"	3 ¹³ /16"	1 15/16"	5/32"	5/32"
1 1/2"	2 13/16"	3 ³ /16"	1 7/8"	⁷ /8"	1 7/16"	5 ⁵ /8"	8 ³ /8"	10 15/16"	8 ³ /8"	4 ¹³ /16"	4 ¹ /2"	2 ¹ /8"	5/32"	5/32"
2"	3 5/16"	3 ¹ /2"	2 3/8"	7/8"	1 1/2"	5 7/8"	8 ¹ /2"	11 ¹ /8"	8 ¹ /2"	5 7/16"	4 ³ /4"	2 1/2"	³ /16"	5/32"
2 ¹ /2"	4 ⁷ /16"	1"	2 ¹⁵ / ₁₆ "	1 ³ /16"	2 ¹ /4"	7 ¹³ / ₁₆ "	10 ¹ /2"	14 ¹ /16"	10 ¹ /2"	7"	1"	3 ¹ /2"	³ /16"	³ / ₁₆ "
3"	4 7/8"	1"	3 1/2"	13/8"	2 ³ /8"	8 ¹ /2"	11 ³ /4"	15 ⁵ /8"	11 ³ /4"	7 ⁷ /8"	1"	3 ¹⁵ / ₁₆ "	³ /16"	³ / ₁₆ "

Distributed by:



Advance Products & Systems, Inc. is not responsible for errors printed in this brochure.